

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
Revision Date Apr 01, 2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name CHLOROFORM

CAS-No. 67-66-3 Product code 05S0025

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production.

1.3 Details of the supplier of the safety data sheet

Company RCI LABSCAN LIMITED.

24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

Telephone number (662) 613-7911-4 Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 3), H331

Skin irritation, (Category 2), H315 Eye irritation, (Category 2), H319

Carcinogenicity, (Category 2), H351

Reproductive toxicity, (Category 2), H361D

Specific Target Organ Toxicity (single exposure), (Category 3), Central nervous system, H336

Specific Target Organ Toxicity (repeated exposure), (Category 1), Liver, Kidney, H372

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word Danger

Hazard statement(s)

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

H361D Suspected of damaging the unborn child.

H372 Causes damage to organs (Liver, Kidney) through prolonged or repeated

exposure.

RCI Labscan Limited. Page 1 of 9

Precautionary statement(s)

P203 Obtain, read and follow all safety instructions before use.

P260 Do not breathe fume/gas/mist/vapours/spray...

P264 Wash hand thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P317 IF SWALLOWED: Get medical help. P302 + P352 IF ON SKIN: Wash with plenty water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P316 Get emergency medical help immediately.
P318 IF exposed or concerned: Get medical advice.

P330 Rinse mouth.

P332 + P317 If skin irritation occurs: Get medical help.
P337 + P317 If eye irritation persists: Get medical help.

P362 + P364 Take off contaminated clothing and wash it before reuse.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms Formyl trichloride, Methane trichloride, Methenyl trichloride, Methyl trichloride,

Trichloromethane

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 67-66-3 200-663-8 602-006-00-4 CHCl₃ 119.38 g/mol >99

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Chloroform		
CAS-No 67-66-3	>99%	Acute toxicity, Oral (Category 4), H302
EC-No 200-663-8		Acute toxicity, Inhalation (Category 3), H331
EC-Index-No 602-006-00-4		Skin irritation, (Category 2), H315
		Eye irritation, (Category 2), H319
		Carcinogenicity, (Category 2), H351
		Reproductive toxicity, (Category 2), H361D
		Specific Target Organ Toxicity (single exposure),
		(Category 3), Central nervous system, H336
		Specific Target Organ Toxicity (repeated exposure),
		(Category 1), Liver, Kidney, H372

For the full text of the H-Statements mentioned in this Section, see Section 16

3.2 Stabilized

Ethanol

Synonyms Ethyl alcohol Denatured, Denatured alcohol, Ethanol Denatured.

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 64-17-5 200-578-6 603-002-00-5 C_2H_5OH 46.07 g/mol <1

RCI Labscan Limited. Page 2 of 9

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Ethanol		
CAS-No 64-17-5	<1%	Flammable liquids (Category 2), H225
EC-No 200-578-6		Eye irritation (Category 2), H319
EC-Index-No 603-002-00-5		

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of
	shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing
	or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose.
	Use suitable instruments/apparatus.
Skin contact	Remove contaminated clothing and wash affected skin with soap and water. If signs of
	poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated
	clothing before reuse. Contaminated combustible material, e.g. clothing ignites more
	readily and burns fiercely.
Eye contact	If the substance has got into the eyes, immediately wash out with plenty of water at least
	15 minutes. Obtain medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. Keep patient warm. In case of shortness of breath,
	give oxygen. Apply artificial respiration only if patient is not breathing or under medical
	supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable
	instruments/apparatus. Obtain medical attention. Never give anything by mouth to an
	unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing: immediately make victim drink plenty of water. Subsequently administer: Activate charcoal 20-40 g in 10% slurry. Laxative: Sodium Sulfate 1 tablespoon/250 ml of water. Indications for the doctor: Gastric lavage. No milk, No castor oil, No alcohol.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In adaption to materials stored in the immediate neighborhood.

5.2 Special hazards arising from the substance or mixture

Non-combustible liquid. Vapors heavier than air. Ambient fire may liberate hazardous vapors. The following may develop in event of fire: Hydrochloric acid, phosgene, chlorine.

5.3 Advice for firefighters

Do not stay in dangerous zone without self-contained breathing apparatus. In order to avoid contact with skin. Keep a safety distance and wear suitable protective clothing.

5.4 Further information

Contain escaping vapors with water. Prevent fire-fighting water from entering surface water or ground water.

RCI Labscan Limited. Page 3 of 9

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Application Area	Health Effects	Exposure	Value
Worker	Acute Systemic effects	Inhalation	333 mg/m³
Worker	Long-term Local effects	Inhalation	2.5 mg/m³
Worker	Long-term Systemic effects	Inhalation	2.5 mg/m³
Worker	Long-term Systemic effects	Skin contact	0.94 mg/kg Body weight
Consumer	Long-term Systemic effects	Inhalation	0.18 mg/m³

Predicted No Effect Concentration (PNEC)

Compartment	Value
Aquatic intermittent release	0.133 mg/l
Fresh water	0.146 mg/l
Fresh water sediment	0.45 mg/kg
Marine sediment	0.09 mg/kg
Marine water	0.015 mg/l
Sewage treatment plant	0.048 mg/l
Soil	0.56 ma/ka

RCI Labscan Limited. Page 4 of 9

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE) Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes.

Handle with gloves

- Full contact wears gloves from viton material.
- Splash contact wears gloves from butyl rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter AX (EN 371).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Form
: Color
Colorless
Odour
Odour Threshold
pH
Not Available
Melting point/range
Boiling point/range
Liquid
Colorless
Nweetish
Not Available
Not Available
63 °C
Boiling point/range
61 °C

Flash point Not flammable
Evaporation rate Not Available
Flammability (solid, gas) Not Available
Explosion limits: lower Not Available
upper Not Available

Vapor Pressure 213 hPa at 20°C

Relative Vapor Density 4.25

Density 1.479 g/ml at 20°C
Water solubility 8 g/l at 20°C
Partition coefficient (n-octanol/water) log Pow: 2.0
Auto-Ignition temperature Not combustible
Decomposition Temperature Not Available
Viscosity 0.56 mPa.s at 20°C
Explosive properties Not Explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

SECTION 10: Stability and reactivity

10.1 Reactivity

Heat-sensitive, light sensitive / decomposition; unsuitable working materials: various plastic, rubber.

RCI Labscan Limited. Page 5 of 9

10.2 Chemical stability

Sensitive to light and heat. Decompose on exposure to light and heat. Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with: strong bases, aluminium (powder), amines, ammonia, alkali/alkaline earth metals, fluorine, oxygen, acetone / alkali, dibenzoyl peroxide, iron powder, sodium amide, sodium hydroxide / methanol, sodium methoxide / methanol, nitromethane, nitrogen dioxide.

The substance can react dangerously with: strong oxidizing agents, water, bis-(dimethylamino)-dimethyltin, potassium tert.-butoxide, metal powder, mineral acids, silicon hydride, triisopropylphosphine.

10.4 Conditions to avoid

Heating and light.

10.5 Incompatible materials

Alkali metals, alkaline earth metals, light metals in powder form, peroxide, fluorine, alcoholates, strong bases, ketones, alkalis, alkalis hydroxide, alcohols, organic nitro compounds, alkali amides, oxygen, alkali oxygen, nitrogen oxides, bis-(dimthylamino)-dimethyl tin, amines, ammonia, phosphine.

10.6 Hazardous decomposition products

Hydrochloric acid, phosgene, chlorine, Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD₅₀ (oral, rat): 695 mg/kg

LD₅₀ (dermal, rabbit): >3980 mg/kg

Acute oral toxicity

Absorption: nausea, vomiting.

Acute inhalation toxicity

Absorption: coughing and dyspnea.

Skin corrosion/irritation

Irritations: drying out effect resulting in rough and chapped skin. Danger of skin absorption.

Serious eye damage/eye irritation

Slight irritation.

Respiratory or skin sensitization

Not Available

Germ cell mutagenicity

Bacterial mutagenicity: Ames test; negative.

Carcinogenicity

The National Cancer Institute (NCI) has found clear evidence for carcinogenicity. Limited evidence of a carcinogenic effect.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Chloroform)

Reproductive toxicity

Not Available

RCI Labscan Limited. Page 6 of 9

Teratogenicity

Not Available

Specific target organ toxicity (STOT) - single exposure

Not Available

Specific target organ toxicity (STOT) - repeated exposure

The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1. - Liver, Kidney

Aspiration hazard

Not Available

Further information

After accidental swallowing the substance may pose a risk of aspiration. Passage into the lung (vomiting) can result in a condition resembling pneumonia (chemical pneumonitis).

After absorption; nausea, vomiting, agitation, spasms, narcosis.

After long-term exposure to the chemical: drop in blood pressure, headache, ataxia (impaired locomotor coordinator), gastrointestinal complaints, cardiovascular disorders.

Damage of liver, kidneys and heart.

The product should be handled with the care usual when dealing with chemicals.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC_{50} L.macrochirus : 18 mg/l/96 h. Toxicity to daphnia EC_{50} Daphnia magna: 79 mg/l/48h.

and other aquatic invertebrates

Toxicity to algae IC_5 Sc.quadricauda: 1100 mg/l/8d. Toxicity to bacteria EC_{50} activated sludge: 1010 mg/l/3h

12.2 Persistence and degradability

Biodegradability No Biodegradation

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) log Pow: 2.0 (experimental).

No appreciable bioaccumulation potential is to be expected

(log P o/w 1-3). Distribution preferentially in air.

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Biological effects: Harmful effect for aquatic organisms. Endangers drinking water supplies if swallowed to enter soil and or waters in large quantities.

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly

RCI Labscan Limited. Page 7 of 9

flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

UN Number 1888

UN proper shipping name CHLOROFORM

Transport hazard class(es) 6.1
Packing group III
Environmental hazards No
Special precautions for user Yes

Sea transport (IMDG)

UN Number 1888

UN proper shipping name CHLOROFORM

Transport hazard class(es) 6.1
Packing group III
Marine pollutant No
Special precautions for user Yes
EmS F-A S-A

Air transport (IATA)

UN Number 1888

UN proper shipping name CHLOROFORM

Transport hazard class(es) 6.1
Packing group III
Environmental hazards No
Special precautions for user No

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureNot Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

RCI Labscan Limited. Page 8 of 9

11004	Table 20 to be dead.
H331	Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361D Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

Recommended restrictions

Take notice of labels and safety data sheets for the working.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

01/04/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.