

## **SAFETY DATA SHEET**

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
Revision Date Aug 15, 2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name ETHANOL CAS-No. 64-17-5

Product code AR1069, BP1069, GP1069, RP1069

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production.

1.3 Details of the manufacturer of the safety data sheet

Manufacturer RCI LABSCAN LIMITED.

24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

Telephone number (662) 613-7911-4 Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225 Eye irritation (Category 2), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 Label elements

## Labelling according Regulation (EC) No 1272/2008

#### Pictogram





Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

RCI Labscan Limited. Page 1 of 8

P337 + P317 If eye irritation persists: Get medical help. P403 + P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards None

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

Synonyms Ethyl alcohol Denatured, Denatured alcohol, Ethanol Denatured.

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 64-17-5 200-578-6 603-002-00-5  $C_2H_5OH$  46.07 g/mol >99

## Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification	
Ethanol			
CAS-No 64-17-5	>99%	Flammable liquids (Category 2), H225	
EC-No 200-578-6		Eye irritation (Category 2), H319	
EC-Index-No 603-002-00-5			

For the full text of the H-Statements mentioned in this Section, see Section 16

#### 3.2 Denatured

## Denatoniumbenzoate

Synonyms N,N-diethyl-N-[2-(2,6-dimethylphenylamino)-2-oxoethyl]-Benzylammonium benzoate

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 3734-33-6 223-095-2 -  $C_{28}H_{34}N_2O_3$  446.5 g/mol <1

## Hazardous ingredients according to Regulation (EC) No 1272/2008

C	omponent	Concentration	Classification	
Denatoniur	nbenzoate			
CAS-No	3734-33-6	<1%	Acute toxicity, Oral (Category 4), H302	
EC-No	223-095-2		Acute toxicity, Inhalation (Category 4), H332	
EC-Index-N	0 -			

For the full text of the H-Statements mentioned in this Section, see Section 16

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of

shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose.

Use suitable instruments/apparatus.

Skin contact Remove contaminated clothing and wash affected skin with soap and water. If signs of

poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more

readily and burns fiercely.

Eye contact If the substance has got into the eyes, immediately wash out with plenty of water at least

15 minutes. Obtain medical attention.

RCI Labscan Limited. Page 2 of 8

Ingestion

Rinse mouth. Do not induce vomiting. Immediately make victim drink water (two glasses at the most). Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

#### 4.3 Indication of any immediate medical attention and special treatment needed

Not Available

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

## Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical, foam or water. In the event of fire, cool tanks with water spray.

### 5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air at ambient temperature. Flash back possible over considerable distance.

## 5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

#### 5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

## 6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

## 6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

## 6.4 Reference to other sections

For disposal see Section 13.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause

RCI Labscan Limited. Page 3 of 8

ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Derived No Effect Level (DNEL)**

Application Area	Health Effects	Exposure	Value
Worker	Acute Local effects	Inhalation	1900 mg/m³
Worker	Long-term Systemic effects	Inhalation	950 mg/m³
Worker	Long-term Systemic effects	Skin contact	343 mg/kg Body weight
Consumer	Acute Local effects	Inhalation	950 mg/m³
Consumer	Long-term Systemic effects	Ingestion	87 mg/kg Body weight
Consumer	Long-term Systemic effects	Inhalation	114 mg/m³
Consumer	Long-term Systemic effects	Skin contact	206 mg/kg Body weight

#### **Predicted No Effect Concentration (PNEC)**

Compartment	Value
Aquatic intermittent release	2.75 mg/l
Fresh water	0.96 mg/l
Fresh water sediment	3.6 mg/kg
Marine water	0.79 mg/l
Oral	720 mg/kg
Sewage treatment plant	580 mg/l
Soil	0.63 mg/kg

## 8.2 Exposure controls

## Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

# Individual protection measures (Personal protective equipment, PPE) Eye/face protection

Goggles giving complete protection to eyes.

#### Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes.

Handle with gloves

- Full contact wears gloves from butyl rubber material.
- Splash contact wears gloves from nitrile rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter A (EN 141 or EN 14387).

## **Environmental exposure controls**

Prevent liquid entering sewers, basements and workpits.

RCI Labscan Limited. Page 4 of 8

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical State

Color

Colorless

Odour

Alcohol-like

Odour Threshold

pH

7.0 at 20°C

Melting point/range

Liquid

Colorless

Alcohol-like

Not Available

7.0 at 20°C

Boiling point/range 78.3 °C at 1013 hPa
Flash point 12 °C (closed cup)
Evaporation rate Not Available
Flammability (solid, gas) Not Available
Explosion limits: lower 3.5 % (V)
upper 15 % (V)

Vapor Pressure 59 hPa at 20°C

Relative Vapor Density 1.6

Density 0.790 g/ml at 20°C
Water solubility Soluble at 20°C
Partition coefficient (n-octanol/water) log Pow: -0.32
Auto-Ignition temperature 425 °C
Decomposition Temperature Not Available
Viscosity 1.2 mPa.s at 20°C
Explosive properties Not Explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

Heat sensitive/decomposition.

## 10.2 Chemical stability

Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

Risk of explosion in contact with chlorine, strong oxidizing agents, nitric acid, calcium hypochlorite, halogen oxides, disulfur difluoride, acetic anhydride + salts + acids, isocyanates, potassium, potassium dioxide, potassium permanganate/sulfuric acid, sodium, sodium hypochloride, sodium peroxide, perchlorates, peracids, perchloro nitrile, mercury nitrate, oxygen (liquid), sulfuric acid + hydrogen peroxide, silver/nitric acid, silver nitrate, silver nitrate/ammonia, silver oxide/ammonia, nitrogen dioxide, conc. hydrogen peroxide.

The substance can react dangerously with alkali/alkaline earth metals, fluorine, reducing agents, acetylene bromide, acetylene chloride, barium perchlorate, bromine trifluoride, chromium trioxide, chromyl chloride, oxiran, iodine heptafluoride, potassium tert.-butoxide, lithium hydride, phosphorus trioxide, platinum black, nitric acid/potassium permanganate, acid anhydrides, acids, uranium hexafluoride, zirconium(IV)-chloride, zirconium(IV)-iodide

## 10.4 Conditions to avoid

Moisture, heat, flames and sparks.

## 10.5 Incompatible materials

Alkali metals, alkaline earth metals, alkali oxides, strong oxidizing agents, halogen-halogen compound, chromyl chloride, ethylene oxide, fluorine, perchlorates, potassium permanganate, sulfuric acid, perchloric acid, permanganic acid, oxides of phosphorus, nitric acid, nitrogen dioxide, uranium hexafluoride, hydrogen peroxide, chromium(VI) oxide.

Unsuitable working materials: various plastics, rubber.

## 10.6 Hazardous decomposition products

Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

 $LC_{50}$  (inhalation, rat): > 95.6 mg/l /4h  $LD_{50}$  (oral, rat): 6200 mg/kg

## Acute oral toxicity

Symptoms: nausea and vomiting

## Acute inhalation toxicity

Slight mucosal irritations.

## Skin corrosion/irritation

Slight irritant

## Serious eye damage/eye irritation

Slight irritant

## Respiratory or skin sensitization

Sensitisation test: Magnusson and Kligman is negative.

## Germ cell mutagenicity

Bacterial mutagenicity; Salmonella typhimurium is negative.

## Carcinogenicity

Not Available

## Reproductive toxicity

Not Available

## **Teratogenicity**

Not Available

## Specific target organ toxicity (STOT) - single exposure

Not Available

## Specific target organ toxicity (STOT) - repeated exposure

Not Available

## **Aspiration hazard**

Not Available

#### **Further information**

After absorption of large quantities; dizziness, inebriation, narcosis, respiratory paralysis.

The product should be handled with the care usual when dealing with chemicals.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxicity to fish LC<sub>50</sub> L.idus: 8140 mg/l /48h.

Toxicity to daphnia EC<sub>50</sub> Daphnia magna: 9268-14221 mg/l/48h

and other aquatic invertebrates

Toxicity to algae  $IC_5$  Sc.quadricauda: 5000 mg/l /7d Toxicity to bacteria  $EC_5$  Ps. Putida: 6500 mg/l /16d.

## 12.2 Persistence and degradability

Biodegradability 94% Readily biodegradable

## 12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) log Pow: -0.32 (experimental).

No Bioaccumulation (log P o/w <1).

## 12.4 Mobility in soil

Not Available

## 12.5 Results of PBT and vPvB assessment

Not Available

#### 12.6 Other adverse effects

Biological effects: In high concentrations; Harmful effect on aquatic organisms. When used properly, no impairments in the function of waste water treatment plant are to be expected.

Do not allow to enter waters, waste water or soil.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

#### Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

## **SECTION 14: Transport information**

## Land Transport (ADR/RID)

UN Number 1170 UN proper shipping name ETHANOL

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user Yes

## Sea transport (IMDG)

UN Number 1170 UN proper shipping name ETHANOL

Transport hazard class(es)

Packing group

Marine pollutant

Special precautions for user

EmS

Symbol Symb

## Air transport (IATA)

UN Number 1170 UN proper shipping name ETHANOL

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user No

#### River transport (AND/ADNR)

(Not examined)

## **SECTION 15: Regulatory information**

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Not Available

## 15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

## **SECTION 16: Other information**

#### Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

#### Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

#### **Further information**

Contact to RCI Labscan Limited.

#### **Revision Date**

15/08/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

RCI Labscan Limited. Page 8 of 8