

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
Revision Date Feb 01, 2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name PETROLEUM ETHER 90-120

CAS-No. 8032-32-4 Product code AR1399

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production

1.3 Details of the supplier of the safety data sheet

Company RCI LABSCAN LIMITED.

24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

Telephone number (662) 613-7911-4 Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315

Specific target organ toxicity - single exposure (Category 3), H336

Aspiration hazard (Category 1), H304 Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram









Signal word

Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P242 Use non-sparking tools.

RCI Labscan Limited. Page 1 of 8

P243	Take action to prevent static discharges.	
P261	Avoid breathing fume/gas/mist/vapours/spray.	
P264	Wash hand thoroughly after handling.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P301 + P316	IF SWALLOWED: Get emergency medical help immediately.	
P302 + P352 IF ON SKIN: Wash with plenty water.		
P303 + P361 + P353	P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skil with water [or shower].	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P319	Get medical help if you feel unwell.	
P331	Do NOT induce vomiting.	
P332 + P317 If skin irritation occurs: Get medical help.		
P362 + P364	P362 + P364 Take off contaminated clothing and wash it before reuse.	
P391	Collect spillage.	
P403 + P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up	

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

Mixture of aliphatic hydrocarbon

Synonyms Petroleum benzine, Petroleum spirit.

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 8032-32-4 232-453-7 649-263-00-9 - - - -

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification	
Mixture of aliphatic hydrocarbon			
CAS-No 8032-32-4	-	Flammable liquids (Category 2), H225	
EC-No 232-453-7		Skin irritation (Category 2), H315	
EC-Index-No 649-263-00-9		Specific target organ toxicity - single exposure (Category	
		3), H336	
		Aspiration hazard (Category 1), H304	
		Chronic aquatic toxicity (Category 2), H411	

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of

shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose.

Use suitable instruments/apparatus.

RCI Labscan Limited. Page 2 of 8

Skin contact Remove contaminated clothing and wash affected skin with soap and water. If signs of

poisoning appear, treat as for inhalation. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more readily and burns fiercely.

If the substance has got into the eyes, immediately wash out with plenty of water at least

15 minutes. Obtain medical attention.

Ingestion Rinse mouth. Do not induce vomiting. Keep patient warm. In case of shortness of breath,

give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an

unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing, avoid vomiting. Risk of aspiration. Keep airways free. Subsequently administer: activated charcoal (20 – 40 g in 10% slurry). In case of spontaneous vomiting: Risk of aspiration. Pulmonary failure possible.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Eye contact

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical or foam. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air at ambient temperature. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Remove all sources of ignition. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed at room temperature in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE) Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes. Handle with gloves

- Full contact wears gloves from nitrile rubber material.
- Splash contact wears gloves from nitrile rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter A (EN 141 or EN 14387).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Form Liquid Colorless : Color Benzene like Odour Odour Threshold Not Available Not Available Not Available Melting point/range Boiling point/range 90-120 °C Flash point Not Available Not Available Evaporation rate

RCI Labscan Limited. Page 4 of 8

Flammability (solid, gas)

Explosion limits: lower

upper

Not Available

Not Available

Vapour Pressure

Not Available

Vapour Pressure Not Available Relative vapour density Not Available

Density 0.685-0.730 g/ml at 20°C

Water solubility Insoluble
Partition coefficient (n-octanol/water) Not Available
Auto-Ignition temperature Not Available
Decomposition Temperature Not Available
Viscosity Not Available
Explosive properties Not Explosive

Oxidizing properties The substance or mixture is not classified as oxidizing

SECTION 10: Stability and reactivity

10.1 Reactivity

Highly flammable.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with strong oxidizing.

The substance can react dangerously with strong oxidizing agents.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents. Unsuitable working materials: Various plastics, rubber.

10.6 Hazardous decomposition products

Carbon monoxides, Carbon dioxides, (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Not Available

Acute oral toxicity

Symptoms: nausea.

Acute inhalation toxicity

Irritation symptoms in the respiratory tract, drowsiness.

Skin corrosion/irritation

Slightly irritations. Drying out effect resulting in rough and chapped skin. Danger of skin absorption.

Serious eye damage/eye irritation

Slight irritations.

RCI Labscan Limited. Page 5 of 8

Respiratory or skin sensitization

Not Available

Germ cell mutagenicity

Not Available

Carcinogenicity

Not Available

Reproductive toxicity

Animal experiments suggest that the substance may lead to an impairment of reproductive performance also man.

Teratogenicity

Not Available

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May cause pneumonia or chemical pneumonitis.

Further information

After accidental swallowing the substance may pose a risk of aspiration. Passage into the lung (vomiting) can result in a condition resembling pneumonia (chemical pneumonitis).

After absorption: Headache, dizziness, agitation, spasms, unconsciousness.

Cannot be excluded: Cardiovascular failure and respiratory paralysis.

Damage of lungs.

The product should be handled with the care usual when dealing with chemicals.

SECTION 12: Ecological information

Mixture

12.1 Toxicity

12.2 Persistence and degradability

Biodegradability Not Available

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) Not Available

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Biological effects: toxic for aquatic organisms. May cause long term adverse effects in the aquatic environment. Do not allow to enter waters, waste water or soil.

RCI Labscan Limited. Page 6 of 8

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

UN Number 1268

UN proper shipping name PETROLEUM DISTILLATES, N.O.S.

Transport hazard class(es) 3
Packing group II
Environmental hazards Yes
Special precautions for user Yes

Sea transport (IMDG)

UN Number 1268

UN proper shipping name PETROLEUM DISTILLATES, N.O.S.

Transport hazard class(es) 3
Packing group II
Marine pollutant Yes
Special precautions for user Yes
EmS F-E S- E

Air transport (IATA)

UN Number 1268

UN proper shipping name PETROLEUM DISTILLATES, N.O.S.

Transport hazard class(es) 3
Packing group II
Environmental hazards Yes
Special precautions for user No

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or Mixture Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

RCI Labscan Limited. Page 7 of 8

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

01/02/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

RCI Labscan Limited. Page 8 of 8