

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
Revision Date Apr 01, 2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name 1, 4 -DIOXAN CAS-No. 123-91-1

Product code AH1060B, AR1059B, RP1059B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production.

1.3 Details of the supplier of the safety data sheet

Company RCI LABSCAN LIMITED.

24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

Telephone number (662) 613-7911-4 Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225 Eye irritation (Category 2), H319 Carcinogenicity (Category 2), H351

Specific target organ toxicity - single exposure (Category 3), H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
EUH019 May form explosive peroxides.

Danger

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P203 Obtain, read and follow all safety instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P242 Use non-sparking tools.

RCI Labscan Limited. Page 1 of 8

P243 Take action to prevent static discharges. P261 Avoid breathing vapours. P264 Wash hand thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P318 IF exposed or concerned: Get medical advice. P337 + P317 If eye irritation persists: Get medical help. P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms 1, 4-Dioxane, Glycolethylether, 1, 4-Diethylene dioxide, 1, 4-Dioxacyclohexane,

Diethylene dioxide, Di(ethylene oxide), Dioxan, Dioxane, Dioxane-1, 4, Dioxan-1, 4, p-Dioxan, Tetrahydro-p-dioxin, Tetrahydro-1, 4-dioxin, Dioxyethylene ether, Glycol ethylene

ether, Diethylene ether.

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 123-91-1 204-661-8 603-024-00-5 $C_4H_8O_2$ 88.11 g/mol <=100

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
1, 4-Dioxan		
CAS-No 123-91-1	<=100%	Flammable liquids (Category 2), H225
EC-No 204-661-8		Eye irritation (Category 2), H319
EC-Index-No 603-024-00-5		Carcinogenicity (Category 2), H351
		Specific target organ toxicity - single exposure (Category
		3), H335

For the full text of the H-Statements mentioned in this Section, see Section 16

3.2 Stabilized

2, 6-Di-tert-butyl-4-methylphenol

Synonyms Butylhydroxytoluene, Butylated hydroxytoluene, 2, 6-di-tert-butyl-p-cresol,

2, 6-Di-tert-butyl-4-methylphenol, 3, 5-Di-tert-butyl-4-hydroxytoluene, BHT

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 128-37-0 204-881-4 - $C_{15}H_{24}O$ 220.36 g/mol <0.0025

Hazardous ingredients according to Regulation (EC) No 1272/2008

C	omponent	Concentration	Classification	
2, 6-Di-tert-butyl-4-methylphenol				
CAS-No	128-37-0	<0.0025%	Acute aquatic toxicity (Category 1), H400	
EC-No	204-881-4		Chronic aquatic toxicity (Category 1), H410	
EC-Index-N	0 -			

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of

shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose.

Use suitable instruments/apparatus.

Skin contact Remove contaminated clothing and wash affected skin with soap and water. If signs of

poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more

readily and burns fiercely.

15 minutes. Obtain medical attention.

Ingestion Rinse mouth. Do not induce vomiting. Immediately make victim drink water (two glasses

at the most) Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing, caution if victim vomits. Risk of aspiration. Keep airways free. Laxative: Sodium Sulfate 1 tablespoon/250 ml of water. Obtain medical attention.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical, foam or water spray. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air at ambient temperature. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE)

Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes.

Handle with gloves

- Full contact wears gloves from butyl rubber material.
- Splash contact wears gloves from viton material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter A (EN 141 or EN 14387).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

RCI Labscan Limited. Page 4 of 8

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: From Liquid
: Color Colorless
Odour Ether like
Odour Threshold Not Available

pH 6-8 at 500g/l of water at 20°C

Melting point/range 12 °C

Boiling point/range 101.5 °C at 1013 hPa
Flash point 11 °C (closed cup)
Evaporation rate Not Available
Flammability (solid, gas) Not Available
Explosion limits: lower 1.7 % (V)
upper 25.2 % (V)

Vapor Pressure 41 hPa at 20°C

Relative Vapor Density 3.03

Density 1.030 g/ml at 20°C
Water solubility Soluble at 20°C
Partition coefficient (n-octanol/water) log Pow: -0.42
Auto-Ignition temperature 375 °C
Decomposition Temperature Not Available
Viscosity 1.32 mPa.s at 20°C

Explosive properties

1.32 mPa.s at 2

Explosive properties

Not Explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

SECTION 10: Stability and reactivity

10.1 Reactivity

Formation of peroxides possible. Incompatible with various plastic, copper compounds.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with air (formation of peroxides), lithium aluminium hydride (heat), Raney-nickel (heat), silver perchlorate, triethylaluminium (heat or drying), nitric acid + perchloric acid, Decaborane (impact).

The substance can react dangerously with oxidizing agents, acids, sulfur trioxide.

10.4 Conditions to avoid

Heating, risk of explosion during distillation.

10.5 Incompatible materials

Hydride, sulfur oxides, perchlorate, triethylaluminium, oxidizing agent, strong acid, air, oxygen, raney-nickel, fire promoting substances.

10.6 Hazardous decomposition products

Peroxide, Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD₅₀ (oral, rat): 5200 mg/kg

 LC_{50} (inhalation, rat): 48.5-54.3 mg/l/4 h LD_{50} (dermal, rabbit): 7600 mg/kg

Acute oral toxicity

Absorption

Symptoms: dizziness, headache, nausea, vomiting (latency time until onset of section).

Systemic effects: damage to liver and kidneys.

Acute inhalation toxicity

Irritation

Symptoms in the respiratory tract: absorption, pulmonary oedema.

Skin corrosion/irritation

Danger of skin absorption. drying out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Irritations to eyes.

Respiratory or skin sensitization

In animal experiments; no sensitizing effect.

Germ cell mutagenicity

Bacterial mutagenicity; Ames test is negative.

Carcinogenicity

The carcinogenic potential requires further clarification.

Reproductive toxicity

Not Available

Teratogenicity

Not Available

Specific target organ toxicity (STOT) - single exposure

May cause respiratory irritation.

Specific target organ toxicity (STOT) - repeated exposure

Not Available

Aspiration hazard

Not Available

Further information

Symptoms: Dizziness, headache, nausea, vomiting. Absorption may result in damage of liver and kidneys.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC_{50} P.promelas: 9850 mg/l /96h. Toxicity to daphnia EC_{50} Daphnia magna: 8450 mg/l/24h.

and other aquatic invertebrates

Toxicity to bacteria EC₅₀ Ps. Putida: 2700 mg/l/16h.

12.2 Persistence and degradability

Biodegradability <5% /28d. Slightly Biodegradable modified OECD screening test.

RCI Labscan Limited. Page 6 of 8

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) log Pow: -0.42 (experimental)

No bioaccumulation is to be expected (log P o/w <1)

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

UN Number 1165
UN proper shipping name DIOXANE

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user Yes

Sea transport (IMDG)

UN Number 1165 UN proper shipping name DIOXANE

Transport hazard class(es)

Packing group

II

Marine pollutant

Special precautions for user

EmS

Second Second

Air transport (IATA)

UN Number 1165 UN proper shipping name DIOXANE

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user No

River transport (AND/ADNR)

(Not examined)

RCI Labscan Limited. Page 7 of 8

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H225	Highly flammable liquid and vapou
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects.

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

01/04/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.