

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS) Revision Date Jul 01, 2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	SULFURIC ACID FUMING
CAS-No.	8014-95-7
Product code	GP1327

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses Chemical for analysis and production.

1.3 Details of the supplier of the safety data sheet

Company	RCI LABSCAN LIMITED. 24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand
Telephone number	(662) 613-7911-4
Fax number	(662) 613-7915

1.4 Emergency Telephone Number Emergency phone

(662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 Corrosive to metals (Category 1), H290 Acute toxicity, Inhalation (Category 2), H330 Skin corrosion (Category 1A), H314 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Danger

Pictogram



Hazard statement(s) H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H330 Fatal if inhaled. H335 May cause respiratory irritation. EUH014 Reacts violently with water. Precautionary statement(s) P234 Keep only in original packaging. P260 Do not breathe dusts or mists. P264 Wash hand thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P284 Wear respiratory protection. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

2.3 Other hazards	None
P406	Store in corrosion resistant/ container with a resistant inner liner.
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P390	Absorb spillage to prevent material-damage.
P363	Wash contaminated clothing before reuse.
P316	Get emergency medical help immediately.
	lenses, if present and easy to do. Continue rinsing.
P305 + P354 + P338	IF IN EYES: Immediately rinse with water for several minutes. Remove contact
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302 + P361 + P354	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Immediately rinse with water for several minutes.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	Oleum				
CAS-No	EC-No	EC-Index-No	Formula	Molecular Weight	Weight %
8014-95-7	231-976-8	016-019-00-2	H ₂ SO ₄ .SO ₃	258.20 g/mol	>99 (Free SO ₃ 28-32)

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Sulfuric acid fuming		
CAS-No 8014-95-7 EC-No 231-976-8 EC-Index-No 016-019-00-2	>99% (Free SO ₃ 28-32%)	Corrosive to metals (Category 1), H290 Acute toxicity, Inhalation (Category 2), H330 Skin corrosion (Category 1A), H314 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Inhalation	Show this safety data sheet to the doctor in attendance. Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus.
Skin contact	Remove contaminated clothing and wash affected skin with soap and water. Dab with polyethylene glycol 400. If signs of poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated clothing before reuse.
Eye contact	If the substance has got into the eyes, immediately wash out with plenty of water at least 15 minutes. Obtain medical attention.
Ingestion	After swallowing: make victim drink water (two glasses at the most), avoid vomiting, risk of perforation. Immediately call in physician. Do not attempt to neutralize.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed Not Available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In adaption to materials stored in the immediate neighborhood.

5.2 Special hazards arising from the substance or mixture

Non-combustible. Ambient fire may liberate hazardous vapors. Hydrogen may form upon contact with metals (danger of explosion). The following may develop in event of fire: Sulfur oxide.

5.3 Advice for firefighters

Do not stay in dangerous zone without self-contained breathing apparatus. In order to avoid contact with skin, keep a safety distance and wear suitable protective clothing.

5.4 Further information

Contain escaping vapors with water. Prevent fire-fighting water from entering surface water or ground water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage : soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits. Transfer to covered drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of good ventilation in the working area. Avoid any contact when handling the substance.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well-ventilated place. Keep out of direct sunlight and away from heat, water and incompatible materials. Requirements for containers, no metal containers.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in ventilation hoods and fans.

Individual protection measures (Personal protective equipment, PPE) Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / corrosive protective clothing, heavy duty work shoes. Handle with gloves

- Full contact wears gloves from viton material.
- Splash contact wears gloves from butyl rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter P2 (EN 141 or EN 14387).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: From	Liquid
: Color	Colorless to light brown
Odour	Not Available
Odour Threshold	Not Available
рН	<1 at 100g/l at 20ºC
Melting point/range	Not Available
Boiling point/range	Not Available
Flash point	Not Available
Evaporation rate	Not Available
Flammability (solid, gas)	Not Available
Explosion limits: lower	Not Available
upper	Not Available
Vapor Pressure	Not Available
Relative Vapor Density	Not Available
Density	1.93 g/ml at 25⁰C
Water solubility	Soluble at 20°C (caution, development of heat)
Partition coefficient (n-octanol/water)	Not Available
Auto-Ignition temperature	Not Available
Decomposition Temperature	Not Available
Viscosity	Not Available
Explosive properties	Not Explosive
Oxidizing properties	Not Available

SECTION 10: Stability and reactivity

10.1 Reactivity

Hygroscopic

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with alkali/alkaline earth metals, alkali and alkaline earth oxides, chlorates, organic

materials, permanganates.

The substance can react dangerously with ammonia, combustible substances

10.4 Conditions to avoid

Exposure to moisture.

10.5 Incompatible materials

Alkali/alkaline earth metals, alkali and alkaline earth oxides, chlorates, organic materials, permanganates, ammonia, combustible substances

10.6 Hazardous decomposition products

Has a corrosive effect incompatible with metals, animals, vegetable tissues. Sulfur oxide, Hydrogen (Hazardous decomposition products from under contact with metals, danger of explosion).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LC50 (Inhalation, rat): 0.696 mg/l/4h

Acute oral toxicity

Severe pain (risk of perforation), nausea, vomiting and diarrhora. After a latency period of several weeks possibly pyloric stenosis.

Acute inhalation toxicity

Damage to the affected mucous membranes.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes burns, risk of blindness.

Respiratory or skin sensitization

Not Available

Germ cell mutagenicity Not Available

Carcinogenicity

Not Available

Reproductive toxicity Not Available

Not Available

Teratogenicity Not Available

Specific target organ toxicity (STOT) - single exposure Not Available

Specific target organ toxicity (STOT) - repeated exposure Not Available

Aspiration hazard Not Available

Further information

The product should be handled with the care usual when dealing with chemicals.

SECTION 12: Ecological information

12.1 Toxicity

Not Available

12.2 Persistence and degradability

Not Available

12.3 Bioaccumulative potential

Not Available

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Harmful effect on aquatic organisms. Harmful effect due to pH shift. Toxic effect on fish and algae. Caustic even in diluted form. Does not cause biological oxygen deficit. Endanger drinking water supplies if allowed to enter soil and/or waters in large quantities. Neutralization possible in waste water treatment plants. Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)	
UN Number	1831
UN proper shipping name	SULPHURIC ACID, FUMING
Transport hazard class(es)	8 (6.1)
Packing group	I
Environmental hazards	No
Special precautions for user	Yes
Sea transport (IMDG)	
Sea transport (IMDG) UN Number	1831
1 \ /	1831 SULPHURIC ACID, FUMING
UN Number	
UN Number UN proper shipping name	SULPHURIC ACID, FUMING
UN Number UN proper shipping name Transport hazard class(es)	SULPHURIC ACID, FUMING

Special precautions for user	Yes
EmS	F-A S-B
Air transport (IATA)	
UN Number	1831
UN proper shipping name	SULPHURIC ACID, FUMING
Transport hazard class(es)	8 (6.1)
Packing group	I
Environmental hazards	No
Special precautions for user	No
Diversion and (AND/ADND)	

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
EUH014	Reacts violently with water.

Recommended restrictions

Take notice of labels and safety data sheets for the working.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

01/07/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.