

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name ELECTROSOLV 211
CAS-No. -
Product code GN1223

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production.

1.3 Details of the supplier of the safety data sheet

Company RCI LABSCAN LIMITED.
24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand
Telephone number (662) 613-7911-4
Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 1), H224
Acute toxicity, Oral (Category 3), H301
Acute toxicity, Dermal (Category 3), H311
Acute toxicity, Inhalation (Category 3), H331
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
Specific target organ toxicity - single exposure (Category 1), Eyes, H370
For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H224 Extremely flammable liquid and vapour.
H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.
H336 May cause drowsiness or dizziness.
H370 Causes damage to organs (eyes).
EUH019 May form explosive peroxides.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.

P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe vapours.
P264	Wash hand thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302 + P352	IF ON SKIN: Wash with plenty water.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P311	IF exposed or concerned: Call a POISON CENTER/ doctor.
P330	Rinse mouth.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use carbon dioxide, dry chemical or foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

Diethyl ether

Synonyms Ethyl ether, Ethyl oxide, Ether, Ethoxyethane

CAS-No	EC-No	EC-Index-No	Formula	Molecular Weight	Weight %
60-29-7	200-467-2	603-022-00-4	(C ₂ H ₅) ₂ O	74.12 g/mol	65-75

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Diethyl ether		
CAS-No 60-29-7 EC-No 200-467-2 EC-Index-No 603-022-00-4	65-75%	Flammable liquids (Category 1), H224 Acute toxicity, oral (Category 4), H302 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Methanol

Synonyms Methyl alcohol, Carbinol, Wood alcohol.

CAS-No	EC-No	EC-Index-No	Formula	Molecular Weight	Weight %
67-56-1	200-659-6	603-001-00-X	CH ₃ OH	32.04 g/mol	25-35

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Methanol		
CAS-No 67-56-1 EC-No 200-659-6 EC-Index-No 603-001-00-X	25-35%	Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Dermal (Category 3), H311 Acute toxicity, Inhalation (Category 3), H331 Specific target organ toxicity - single exposure (Category 1), Eyes, H370

For the full text of the H-Statements mentioned in this Section, see Section 16

3.3 Stabilized

2,6-Di-tert-butyl-4-methylphenol

Synonyms Butylhydroxytoluene, Butylated hydroxytoluene, 2,6-di-tert-butyl-p-cresol, 2,6-Di-tert-butyl-4-methylphenol, 3,5-Di-tert-butyl-4-hydroxytoluene, BHT

CAS-No	EC-No	EC-Index-No	Formula	Molecular Weight	Weight %
128-37-0	204-881-4	-	C ₁₅ H ₂₄ O	220.36 g/mol	<0.0005

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
2,6-Di-tert-butyl-4-methylphenol		
CAS-No 128-37-0	<0.0005%	Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410
EC-No 204-881-4		
EC-Index-No -		

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus.
Skin contact	Remove contaminated clothing and wash affected skin with soap and water. If signs of poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more readily and burns fiercely.
Eye contact	If the substance has got into the eyes, immediately wash out with plenty of water at least 15 minutes. Obtain medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. Immediately make victim drink water (two glasses at the most) Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing, make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call in physician, mentioning methanol ingestion. If breathing stops. Mouth to mouth respiration or mechanical ventilation.

In case of spontaneous vomiting: risk of aspiration. Pulmonary failure possible.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical foam or water spray. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see **Section 13**.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep at +15 °C to +25 °C. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE)**Eye/face protection**

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes.

Handle with gloves

- Splash contact wears gloves from viton material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter AX (EN 371).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance: Form	Liquid
: Color	Colorless
Odour	Characteristic
Odour Threshold	Not Available
pH	Not Available
Melting point/range	Not Available
Boiling point/range	Not Available
Flash point	Not Available
Evaporation rate	Not Available
Flammability (solid, gas)	Not Available
Explosion limits: lower	Not Available
upper	Not Available
Vapor Pressure	Not Available
Relative Vapor Density	Not Available
Density	Not Available
Water solubility	Not Available
Partition coefficient (n-octanol/water)	Not Available
Auto-Ignition temperature	Not Available
Decomposition Temperature	Not Available
Viscosity	Not Available
Explosive properties	Not Explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Heat-sensitive, light sensitive, sensitive to air; unsuitable working materials: various plastic, rubber. Explosible with air in a vaporous/gaseous state.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with bromine, chlorine, air (formation of peroxides), strong oxidizing agents, nitric

acid, oxygen, sulfuric acid, hydrogen peroxide, alkaliperchlorates, boron triazide, bromine fluorides, chromium trioxide, fluoronitrate, liquid oxygen, nitrosyl perchlorate, nitryl perchlorate, ozone, perchloric acid, perchloryl nitrile, permanganic acid, peroxydisulfuric acid, sulphur (heat), oil of turpentine, uranyl nitrate/light.

The substance can react dangerously with aluminium ethoxide/air, bromine azide, chlorine trifluoride, chromyl chloride, iodine heptafluoride, iodine(VIII)oxide, sodium peroxide, silver perchlorate, sulphuryl chlorid, uranyl acetate, zirconium tetrachloride.

The substance forms an explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Halogens, halogen-halogen compounds, azide, nonmetals, nonmetallic oxyhalides, strong oxidizing agent, CrO₃, halogen oxides, peroxi compounds, perchloric acid, perchlorate, nitric acid, oxygen, ozone, chromyl chloride, turpentine oils and/or turpentine substitutes, nitrate.

10.6 Hazardous decomposition products

Peroxide, Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Not Available

Acute oral toxicity

Absorption

Symptoms : may pose a risk of aspiration upon vomiting., Asperation may cause pulmonary oedema and pneumonitis.

Acute inhalation toxicity

Absorption

Symptoms: mucosal irritations, drowsiness and dizziness.

Skin corrosion/irritation

Irritation: drying out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Slight irritations.

Respiratory or skin sensitization

Not Available

Germ cell mutagenicity

Not Available

Carcinogenicity

Not Available

Reproductive toxicity

Not Available

Teratogenicity

Not Available

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

Not Available

Aspiration hazard

Not Available

Further information

After absorption : salivation, euphoria, ataxia (impaired locomotor coordination), inebriation, collapse, unconsciousness, coma. Can't be excluded: respiratory paralysis, death.

Passage into the lung (vomiting) can result in a condition resembling pneumonia (chemical pneumonitis).

The product should be handled with the care usual when dealing with chemicals.

SECTION 12: Ecological information**Mixture****12.1 Toxicity**

Not Available

12.2 Persistence and degradability

Biodegradability Not Available

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) Not Available

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information**Land Transport (ADR/RID)**

UN Number	1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (METHANOL, DIETHYL ETHER)
Transport hazard class(es)	3

Packing group	I
Environmental hazards	No
Special precautions for user	Yes

Sea transport (IMDG)

UN Number	1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (METHANOL, DIETHYL ETHER)
Transport hazard class(es)	3
Packing group	I
Marine pollutant	No
Special precautions for user	Yes
EmS	F-E S-E

Air transport (IATA)

UN Number	1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (METHANOL, DIETHYL ETHER)
Transport hazard class(es)	3
Packing group	I
Environmental hazards	No
Special precautions for user	No

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information**Full text of H-Statements referred to under sections 2 and 3**

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).
Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.
Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany,
Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

01/08/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.