

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
Revision Date Nov 03, 2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name ELECTROSOLV 227

CAS-No. -

Product code GN1432

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production.

1.3 Details of the supplier of the safety data sheet

Company RCI LABSCAN LIMITED.

24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

Telephone number (662) 613-7911-4 Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225 Eye irritation (Category 2), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram





Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.
P264 Wash hand thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

RCI Labscan Limited. Page 1 of 9

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use carbon dioxide, dry chemical or foam to extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

Ethanol

Synonyms Ethyl alcohol Denatured, Denatured alcohol, Ethanol Denatured.

CAS-No EC-No EC-Index-No Formula Molecular Weight Volume % 64-17-5 200-578-6 603-002-00-5 C_2H_5OH 46.07 g/mol 95.1 - 96.9

Hazardous ingredients according to Regulation (EC) No 1272/2008

Com	nponent	Concentration	Classification
Ethanol			
CAS-No 6	64-17-5	95.1 - 96.9%	Flammable liquids (Category 2), H225
EC-No 2	200-578-6		Eye irritation (Category 2), H319
EC-Index-No 603-002-00-5			

3.3 Denatured

Denatoniumbenzoate

Synonyms N,N-diethyl-N-[2-(2,6-dimethylphenylamino)-2-oxoethyl]-Benzylammonium benzoate

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 3734-33-6 223-095-2 - $C_{28}H_{34}N_2O_3$ 446.5 g/mol <1

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component		Concentration	Classification
Denatoniu	mbenzoate		
CAS-No	3734-33-6	<1%	Acute toxicity, Oral (Category 4), H302
EC-No	223-095-2		Acute toxicity, Inhalation (Category 4), H332
EC-Index-N	No -		

Tert-Butyl alcohol

Synonyms 2-Methyl-2-propanol, Trimethyl carbinol, tert-Butanol

CAS-No EC-No EC-Index-No Formula Molecular Weight Volume % 75-65-0 200-889-7 603-005-00-1 $C_4H_{10}O$ 74.12 g/mol 0.15

RCI Labscan Limited. Page 2 of 9

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Tert-Butyl alcohol		
CAS-No 75-65-0 FC-No 200-889-7	0.15%	Flammable liquids (Category 2), H225
EC-No 200-889-7 EC-Index-No 603-005-00-1		Acute toxicity, Inhalation (Category 4), H332 Eye irritation (Category 2), H319
		Specific target organ toxicity - single exposure (Category
		3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Inhalation	Show this safety data sheet to the doctor in attendance. Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus.
Skin contact	Remove contaminated clothing and wash affected skin with soap and water. If signs of poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more readily and burns fiercely.
Eye contact	If the substance has got into the eyes, immediately wash out with plenty of water at least 15 minutes. Obtain medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. Immediately make victim drink water (two glasses at the most). Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

Not Available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical, foam or water. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

RCI Labscan Limited. Page 3 of 9

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Application Area	Health Effects	Exposure	Value
Worker	Acute Local effects	Inhalation	1900 mg/m³
Worker	Long-term Systemic effects	Inhalation	950 mg/m³
Worker	Long-term Systemic effects	Skin contact	343 mg/kg Body weight
Consumer	Acute Local effects	Inhalation	950 mg/m³
Consumer	Long-term Systemic effects	Ingestion	87 mg/kg Body weight
Consumer	Long-term Systemic effects	Inhalation	114 mg/m³
Consumer	Long-term Systemic effects	Skin contact	206 mg/kg Body weight

Predicted No Effect Concentration (PNEC)

Compartment	Value
Aquatic intermittent release	2.75 mg/l
Fresh water	0.96 mg/l
Fresh water sediment	3.6 mg/kg
Marine water	0.79 mg/l
Oral	720 mg/kg
Sewage treatment plant	580 mg/l

RCI Labscan Limited. Page 4 of 9

Soil 0.63 mg/kg

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE) Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes. Handle with gloves

- Full contact wears gloves from butyl rubber material.
- Splash contact wears gloves from nitrile rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter A (EN 141 or EN 14387).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Form Liquid Colorless : Color Odour Alcohol-like Odour Threshold Not Available Not Available pН Melting point/range Not Available Boiling point/range Not Available Flash point Not Available Evaporation rate Not Available Flammability (solid, gas) Not Available Not Available Explosion limits: lower Not Available upper Vapor Pressure Not Available Relative Vapor Density Not Available

Density 0.805 - 0.812 g/ml at 20°C

Water solubility

Partition coefficient (n-octanol/water)

Auto-Ignition temperature

Decomposition Temperature

Viscosity

Not Available

Not Available

Not Available

Not Available

Not Available

Not Explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

RCI Labscan Limited. Page 5 of 9

SECTION 10: Stability and reactivity

10.1 Reactivity

Heat sensitive/decomposition. Explosible with air in a vaporous/ gaseous state.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with chlorine, strong oxidizing agents, nitric acid, calcium hypochlorite, halogen oxides, disulphur difluoride, acetic anhydride + salts + acids, isocyanates, potassium, potassium dioxide, potassium permanganate/sulfuric acid, sodium, sodium hypochloride, sodium peroxide, perchlorates, peracids, perchloro nitrile, mercury nitrate, oxygen (liquid), sulfuric acid + hydrogen peroxide, silver/nitric acid, silver nitrate, silver nitrate/ammonia, silver oxide/ammonia, nitrogen dioxide, conc. hydrogen peroxide.

The substance can react dangerously with alkali/alkaline earth metals, fluorine, reducing agents, acetylene bromide, acetylene chloride, barium perchlorate, bromine trifluoride, chromium trioxide, chromyl chloride, oxiran, iodine heptafluoride, potassium tert.-butoxide, lithium hydride, phosphorus trioxide, platinum black, nitric acid/potassium permanganate, acid anhydrides, acids, uranium hexafluoride, zirconium(IV)-chloride, zirconium(IV)-iodide

The substance forms an explosive mixture with air.

10.4 Conditions to avoid

Moisture, heat, flames and sparks.

10.5 Incompatible materials

Alkali metals, alkaline earth metals, alkali oxides, strong oxidizing agents, halogen-halogen compound, chromyl chloride, ethylene oxide, fluorine, perchlorates, potassium permanganate, sulfuric acid, perchloric acid, permanganic acid, oxides of phosphorus, nitric acid, nitrogen dioxide, uranium hexafluoride, hydrogen peroxide, chromium(VI) oxide.

Unsuitable working materials: various plastics, rubber.

10.6 Hazardous decomposition products

Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

 LC_{50} (inhalation, rat): > 95.6 mg/l /4h LD_{50} (oral, rat): 6200 mg/kg

Acute oral toxicity

Symptoms: nausea and vomiting

Acute inhalation toxicity

Slight mucosal irritations.

Skin corrosion/irritation

Slight irritant

Serious eye damage/eye irritation

Slight irritant

Respiratory or skin sensitization

Sensitisation test: Magnusson and Kligman is negative.

RCI Labscan Limited. Page 6 of 9

Germ cell mutagenicity

Bacterial mutagenicity; Salmonella typhimurium is negative.

Carcinogenicity

Not Available

Reproductive toxicity

Not Available

Teratogenicity

Not Available

Specific target organ toxicity (STOT) - single exposure

Not Available

Specific target organ toxicity (STOT) - repeated exposure

Not Available

Aspiration hazard

Not Available

Further information

After absorption of large quantities; dizziness, inebriation, narcosis, respiratory paralysis.

The product should be handled with the care usual when dealing with chemicals.

SECTION 12: Ecological information

Mixture

12.1 Toxicity

Toxicity to fish LC₅₀ L.idus: 8140 mg/l /48h.

Toxicity to daphnia EC₅₀ Daphnia magna: 9268-14221 mg/l/48h

and other aquatic invertebrates

Toxicity to algae IC_5 Sc.quadricauda: 5000 mg/l /7d Toxicity to bacteria EC_5 Ps. Putida: 6500 mg/l /16d.

12.2 Persistence and degradability

Biodegradability 94% Readily biodegradable

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) log Pow: -0.32 (experimental).

No Bioaccumulation (log P o/w <1).

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Biological effects: In high concentrations; Harmful effect on aquatic organisms. When used properly, no impairments in the function of waste water treatment plant are to be expected.

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through

RCI Labscan Limited. Page 7 of 9

corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

UN Number 1170

UN proper shipping name ETHANOL, SOLUTION

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user Yes

Sea transport (IMDG)

UN Number 1170

UN proper shipping name ETHANOL, SOLUTION

Transport hazard class(es)

Packing group

Marine pollutant

Special precautions for user

EmS

Second Seco

Air transport (IATA)

UN Number 1170

UN proper shipping name ETHANOL, SOLUTION

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user No

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H225 Highly flammable liquid and vapour.

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

03/11/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

RCI Labscan Limited. Page 9 of 9