

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
Revision Date Feb 03, 2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name ACETONITRILE

CAS-No. 75-05-8

Product code AH1008, AH1009, AH1010, AR1005, BP1005, DN1008, GP1005,

IR1005, LC1005, LC1007, LC1219, LC1386, LM1005, LV1005, RC1005, RC1005

PC1005, PS1005, RP1005, SG1005, SG1006, UM1005

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production

1.3 Details of the manufacturer of the safety data sheet

Manufacturer RCI LABSCAN LIMITED.

24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

Telephone number (662) 613-7911-4 Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Dermal (Category 4), H312 Acute toxicity, Inhalation (Category 4), H332

Eye irritation (Category 2), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram





Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H302+ H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.

H319 Causes serious eye irritation.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing fume/gas/mist/vapours/spray.

P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.
P270 Do not eat, drink or smoke when using this product.

RCI Labscan Limited. Page 1 of 8

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P317 IF SWALLOWED: Get medical help.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P330 Rinse mouth.

P337 + P317 If eye irritation persists: Get medical help.

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms Methyl cyanide, Cyanomethane, Ethanenitrile.

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 75-05-8 200-835-2 608-001-00-3 CH_3CN 41.05 g/mol <=100

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component		Concentration	Classification		
Acetonitrile					
CAS-No 75	-05-8	<=100%	Flammable liquids (Category 2), H225		
EC-No 20	0-835-2		Acute toxicity, Oral (Category 4), H302		
EC-Index-No 608-001-00-3			Acute toxicity, Dermal (Category 4), H312		
			Acute toxicity, Inhalation (Category 4), H332		
			Eye irritation (Category 2), H319		

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of

shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose.

Use suitable instruments/apparatus.

Skin contact Remove contaminated clothing and wash affected skin with soap and water. Obtain

medical attention. If signs of poisoning appear, treat as for inhalation. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more

readily and burns fiercely.

Eye contact If the substance has got into the eyes, immediately wash out with plenty of water at least

15 minutes. Obtain medical attention.

Ingestion Rinse mouth. Immediately make victim drink water (two glasses at most). Do not induce

vomit. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial

respiration only of patient is mouth to mouth or mouth to nose. Use suitable

instruments/apparatus. Obtain medical attention. Never give anything by mouth to an

unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

Treat as cyanide poisoning. Always have a cyanide first-aid kit and proper instruction on hand. The oneself symptoms is generally delayed pending conversation to Cyanide, Nausea, Vomit, Headache, Dizziness, Rash, Cyanosis, Excitement, Depression, Drowsiness, Impaired Judgment, Lack of Coordination, Stupor and Death.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical, foam or water spray. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air at ambient temperature. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Remove all sources of ignition. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil or vegetation, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

RCI Labscan Limited. Page 3 of 8

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

Storage class 3; Flammable liquids.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Application Area	Health Effects	Exposure	Value
Worker	Acute Local effects	Inhalation	68 mg/m³
Worker	Acute Systemic effects	Inhalation	68 mg/m³
Worker	Long-term Local effects	Inhalation	68 mg/m³
Worker	Long-term Systemic effects	Inhalation	68 mg/m³
Worker	Long-term Systemic effects	Skin contact	32.2 mg/kg Body weight
Consumer	Acute Local effects	Inhalation	22 mg/m³
Consumer	Acute Systemic effects	Ingestion	0.6 mg/kg Body weight
Consumer	Acute Systemic effects	Inhalation	220 mg/m ³
Consumer	Long-term Local effects	Inhalation	4.8 mg/m ³
Consumer	Long-term Systemic effects	Inhalation	4.8 mg/m³

Predicted No Effect Concentration (PNEC)

Compartment	Value
Fresh water	10 mg/l
Fresh water sediment	7.53 mg/kg
Marine water	1 mg/l
Sewage treatment plant	32 mg/l
Soil	2.41 mg/kg
Water	10 ma/l

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE) Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

 $Chemical\ resistant\ apron\ /\ flame\ retardant\ antistatic\ protective\ clothing,\ heavy\ duty\ work\ shoes.$

Handle with gloves

- Full contact wears gloves from butyl rubber material.
- Splash contact wears gloves from polychloroprene material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter A (EN 141 or EN 14387).

RCI Labscan Limited. Page 4 of 8

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical State
Color
Colorless
Odor
Ether-like
Odor Threshold
pH
Not Available
Melting point/range
Boiling point/range
81.6°C

Flash point

Evaporation rate

Flammability (solid, gas)

Explosion limits: lower

upper

2.0 °C (closed cup)

Not Available

Not Available

3.0 %(V)

17 %(V)

Vapor Pressure 97 hPa at 20°C

Relative vapor density 1.42

Density 0.786 g/ml at 20°C
Water solubility Soluble at 20°C
Partition coefficient (n-octanol/water) log Pow: -0.34
Auto-Ignition temperature 523 °C
Decomposition Temperature Not Available
Viscosity 0.316 mPa.s at 25°C
Explosive properties Not Explosive

Oxidizing properties The substance or mixture is not classified as oxidizing

SECTION 10: Stability and reactivity

10.1 Reactivity

Heat-sensitive/decomposition.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with sulfuric acid/heat, cyanopropyl nitrate, perchloric acid, metal perchlorates, nitrogen-fluorine-compounds.

The substance can react dangerously with oxidizing agents, acids, perfluoro urea, nitrogen dioxide/catalyst.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Acid, Bases, Oxidizing agents, Reducing agents.
Unsuitable working materials: various plastics, rubber

10.6 Hazardous decomposition products

Nitrogen oxides (NOX), carbon oxides, Hydrogen cyanide, Hydrocyanic acid (Hazardous decomposition products from under fire condition).

RCI Labscan Limited. Page 5 of 8

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD₅₀ (oral, rat): 617 mg/kg

 LD_{50} (dermal, estimate): 1500 mg/kg LC_{50} (inhalation, rat): 6022 mg/l/4 h

Skin corrosion/irritation

No skin irritation.

Serious eye damage/eye irritation

Irritations

Respiratory or skin sensitization

Not Available

Germ cell mutagenicity

Not Available

Carcinogenicity

Not Available

Reproductive toxicity

Not Available

Specific target organ toxicity (STOT) - single exposure

Not Available

Specific target organ toxicity (STOT) - repeated exposure

Not Available

Aspiration hazard

Not Available

Further information

Systemic effects: nausea, vomiting, headache, dizziness, spasms, unconsciousness, respiratory arrest, cardiac arrest, dyspnea.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC_{50} P.promelas: 1640 mg/l /96h Toxicity to daphnia EC_{50} Daphnia magna: >10000 mg/l /24h

and other aquatic invertebrates

Toxicity to algae IC_5 Sc.quadricauda: 7300 mg/l/8d Toxicity to bacteria EC_5 Ps. Putida: 680 mg/l /16d

12.2 Persistence and degradability

Biodegradability 98%/28 d, Readily biodegradable, according to appropriate OECD test.

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) log Pow: -0.34

No bioaccumulation is to be expected (log P o/w <1)

12.4 Mobility in soil

Not Available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

UN Number 1648

UN proper shipping name ACETONITRILE

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user Yes

Sea transport (IMDG)

UN Number 1648

UN proper shipping name ACETONITRILE

Transport hazard class(es)

Packing group

Marine pollutant

Special precautions for user

EmS

Second Seco

Air transport (IATA)

UN Number 1648

UN proper shipping name ACETONITRILE

Transport hazard class(es) 3
Packing group II
Environmental hazards No
Special precautions for user No

River transport (AND/ADNR)

(Not examined)

RCI Labscan Limited. Page 7 of 8

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or Mixture Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

03/02/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

RCI Labscan Limited. Page 8 of 8