

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
Revision Date Feb 10, 2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name CYCLOHEXANE

CAS-No. 110-82-7

Product code AR1033, GP1033, IR1033, LC1033, LV1033, PC1033, RP1033,

XP1033

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Chemical for analysis and production.

1.3 Details of the manufacturer of the safety data sheet

Manufacturer RCI LABSCAN LIMITED.

24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

Telephone number (662) 613-7911-4 Fax number (662) 613-7915

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Skin irritation (Category 2), H315

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram









Signal word

Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing fume/gas/mist/vapours/spray.

RCI Labscan Limited. Page 1 of 8

P264 Wash hand thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P316 IF SWALLOWED: Get emergency medical help immediately.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331 Do NOT induce vomiting.

P391 Collect spillage.

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms Hexahydrobenzene, Hexamethylene.

CAS-No EC-No EC-Index-No Formula Molecular Weight Weight % 110-82-7 203-806-2 601-017-00-1 C₆H₁₂ 84.16 g/mol <=100

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Cyclohexane		
CAS-No 110-82-7	<=100%	Flammable liquids (Category 2), H225
EC-No 203-806-2		Skin irritation (Category 2), H315
EC-Index-No 601-017-00-1		Specific target organ toxicity - single exposure (Category
		3), Central nervous system, H336
		Aspiration hazard (Category 1), H304
		Acute aquatic toxicity (Category 1), H400
		Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of

shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose.

Use suitable instruments/apparatus.

Skin contact Remove contaminated clothing and wash affected skin with soap and water. If signs of

poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more

readily and burns fiercely.

Eye contact If the substance has got into the eyes, immediately wash out with plenty of water at least

15 minutes. Obtain medical attention.

Ingestion Rinse mouth. Do not induce vomiting. Keep patient warm. In case of shortness of breath,

give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an

unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing, caution if victim vomits. Risk of aspiration. Keep airways free. In case of spontaneous vomiting: Risk of aspiration. Pulmonary failure possible. Call in physician.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical or foam. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air at ambient temperature. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

RCI Labscan Limited. Page 3 of 8

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

Storage class 3; Flammable liquids.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Application Area	Health Effects	Exposure	Value
Worker	Acute Local effects	Inhalation	700 mg/m³
Worker	Acute Systemic effects	Inhalation	700 mg/m³
Worker	Long-term Local effects	Inhalation	700 mg/m³
Worker	Long-term Systemic effects	Inhalation	700 mg/m³
Worker	Long-term Systemic effects	Skin contact	2016 mg/kg Body weight
Consumer	Acute Local effects	Inhalation	412 mg/m³
Consumer	Acute Systemic effects	Inhalation	412 mg/m³
Consumer	Long-term Local effects	Inhalation	206 mg/m ³
Consumer	Long-term Systemic effects	Ingestion	59.4 mg/kg Body weight
Consumer	Long-term Systemic effects	Inhalation	206 mg/m ³
Consumer	Long-term Systemic effects	Skin contact	1186 mg/kg Body weight

Predicted No Effect Concentration (PNEC)

Compartment	Value
Aquatic intermittent release	3.627 mg/kg
Fresh water	0.207 mg/l
Fresh water sediment	3.627 mg/kg
Marine water	0.207 mg/l
Sewage treatment plant	3.24 mg/l
Soil	2.99 mg/kg

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE)

Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes. Handle with gloves

- Full contact wears gloves from nitrile rubber material.
- Splash contact wears gloves from nitrile rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter A (EN 141 or EN 14387).

RCI Labscan Limited. Page 4 of 8

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical State Liquid
Color Colorless
Odour Characteristic
Odour Threshold Not Available
pH Not Available

Melting point/range 6 °C

Boiling point/range 81 °C at 1013 hPa
Flash point -18 °C (closed cup)
Evaporation rate Not Available
Flammability (solid, gas) Not Available
Explosion limits: lower 1.2 % (V)
upper 8.3 % (V)

Vapor Pressure 103 hPa at 20°C

Relative Vapor Density 2.9

Density 0.779 g/ml at 20°C
Water solubility 55 mg/l at 20°C
Partition coefficient (n-octanol/water) log Pow: 3.44
Auto-Ignition temperature 260 °C
Decomposition Temperature Not Available
Viscosity 0.98 mPa.s at 20°C

Explosive properties Not Explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

SECTION 10: Stability and reactivity

10.1 Reactivity

Heat sensitive. Unsuitable working materials: Various plastic, rubber.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with: nitrogen dioxide (liquid/heat).

The substance can react dangerously with: oxidizing agents.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents, nitrogen dioxide.

10.6 Hazardous decomposition products

Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

RCI Labscan Limited. Page 5 of 8

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LC₅₀ (inhalation, rat): 14 mg/l /4h LD₅₀ (oral, rat): 5000 mg/kg LD₅₀ (dermal, rabbit): >2000 mg/kg

Skin corrosion/irritation

Irritations

Serious eye damage/eye irritation

Not Available

Respiratory or skin sensitization

Not Available

Germ cell mutagenicity

Not Available

Carcinogenicity

Not Available

Reproductive toxicity

Not Available

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

Not Available

Aspiration hazard

May cause pulmonary edema and pneumonitis.

Further information

Damage of lungs. The product should be handled with the care usual when dealing with chemicals.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC_{50} L.macrochirus: 34 mg/l /96h. Toxicity to daphnia EC_{50} Daphnia magna: 3.78 mg/l /48h.

and other aquatic invertebrates

Toxicity to algae IC₅₀ Desmodesmus subspicatus: >500 mg/l/72h.

Toxicity to bacteria EC₅₀ Photobacterium phosphoreum: 200 mg/l/5min. microtox test.

12.2 Persistence and degradability

Biodegradability 6% /28d. Slightly biodegradable.

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) log Pow: 3.44 (experimental).

An appreciable bioaccumulation potencial is to be expected

(log P o/w >3).

RCI Labscan Limited. Page 6 of 8

12.4 Mobility in soil

Not Available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

High toxic for aquatic organisms. May cause long term adverse effects in the aquatic environment. Endangers drinking water supplies if swallowed to enter soil and/or water in large quantities. Change in the flavour characteristic of fish protein.

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

UN Number 1145

UN proper shipping name CYCLOHEXANE

Transport hazard class(es) 3
Packing group II
Environmental hazards Yes
Special precautions for user Yes

Sea transport (IMDG)

UN Number 1145

UN proper shipping name CYCLOHEXANE

Transport hazard class(es) 3
Packing group II
Marine pollutant Yes
Special precautions for user Yes
EmS F-E S-D

Air transport (IATA)

UN Number 1145

UN proper shipping name CYCLOHEXANE

Transport hazard class(es) 3
Packing group II
Environmental hazards Yes
Special precautions for user No

RCI Labscan Limited. Page 7 of 8

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

10/02/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

RCI Labscan Limited. Page 8 of 8