

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	ACETONE
CAS-No.	67-64-1
Product code	AR1003, AR1003I, AR1003V, BP1003, EP1003, GM1003, GP1003, IR1003, LC1003, LC1004, LV1003, PC1003, PS1003, RP1003, SM1003, XP1003, XP1003S, VL1003

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Chemical for analysis and production
-----------------	--------------------------------------

1.3 Details of the manufacturer of the safety data sheet

Manufacturer	RCI LABSCAN LIMITED. 24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand
Telephone number	(662) 613-7911-4
Fax number	(662) 613-7915

1.4 Emergency Telephone Number

Emergency phone	(662) 613-7911-4
-----------------	------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Eye irritation (Category 2), H319

Specific target organ toxicity - single exposure (Category 3), H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word	Danger
-------------	--------

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing fume/gas/mist/vapours/spray.

P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P319	Get medical help if you feel unwell.
P337 + P317	If eye irritation persists: Get medical help.

2.3 Other hazards	None
-------------------	------

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms 2-Propanone, Dimethyl ketone, β -Keto-propane

CAS-No	EC-No	EC-Index-No	Formula	Molecular Weight	Weight %
67-64-1	200-662-2	606-001-00-8	CH_3COCH_3	58.08 g/mol	<=100

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Concentration	Classification
Acetone		
CAS-No 67-64-1	<=100%	Flammable liquids (Category 2), H225
EC-No 200-662-2		Eye irritation (Category 2), H319
EC-Index-No 606-001-00-8		Specific target organ toxicity - single exposure (Category 3), H336

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus.
Skin contact	Remove contaminated clothing and wash affected skin with soap and water. Obtain medical attention. If signs of poisoning appear, treat as for inhalation. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more readily and burns fiercely.
Eye contact	If the substance has got into the eyes, immediately wash out with plenty of water at least 15 minutes. Obtain medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11.

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing: immediately make victim drink plenty of water. Subsequently administer: Activate charcoal 20-40 g in 10% slurry. Laxative: Sodium Sulfate 1 tablespoon/250 ml of water. No milk, No castor oil, No alcohol.

Indications for the doctor: Gastric lavage.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical, foam or water spray. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air at ambient temperature. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Remove all sources of ignition. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

Storage class 3; Flammable liquids.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Application Area	Health Effects	Exposure	Value
Worker	Acute Local effects	Inhalation	2420 mg/m ³
Worker	Long-term Systemic effects	Inhalation	1210 mg/m ³
Worker	Long-term Systemic effects	Skin contact	186 mg/kg Body weight
Consumer	Long-term Systemic effects	Skin contact	62 mg/kg Body weight
Consumer	Long-term Systemic effects	Inhalation	200 mg/m ³
Consumer	Long-term Systemic effects	Ingestion	62 mg/kg Body weight

Predicted No Effect Concentration (PNEC)

Compartment	Value
Fresh water	10.6 mg/l
Fresh water sediment	30.4 mg/kg
Marine water	1.06 mg/l
Marine sediment	3.04 mg/kg
Sewage treatment plant	100 mg/l
Soil	29.5 mg/kg

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE)

Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes.

Handle with gloves

- Full contact wears gloves from butyl rubber material.
- Splash contact wears gloves from natural rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter AX (EN 371).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical State	Liquid
Color	Colorless
Odor	Characteristic
Odor Threshold	Not Available

pH	5 – 6 at 395g/l H ₂ O
Melting point/range	-95.4°C
Boiling point/range	56.2°C
Flash point	-20°C (closed cup)
Evaporation rate	Not Available
Flammability (solid, gas)	Not Available
Explosion limits: lower	2.6 %(V)
upper	13 %(V)
Vapor Pressure	233 hPa at 20°C
Relative vapor density	2.01
Density	0.790 g/ml at 20°C
Water solubility	Soluble at 20°C
Partition coefficient (n-octanol/water)	log Pow: 0.24
Auto-Ignition temperature	465°C
Decomposition Temperature	Not Available
Viscosity	0.33 mPa.s at 20°C
Explosive properties	Not Explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

SECTION 10: Stability and reactivity

10.1 Reactivity

Light-sensitive; sensitive to air, solvent.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with hydrogen peroxide, strong oxidizing agents, bromine trifluoride, difluorine dioxide, 2-methyl-1,3-butadiene (isoprene), nitromethane, nitrosyl chloride (catalyst), nitrosyl perchlorate, peroxy monosulfuric acid.

The substance can react dangerously with alkali hydroxide, bromine, fluorine, sodium, strong oxidizing agents, strong reducing agents, nitric acid, chromosulfuric acid, chromium trioxide, chromyl chloride, ethanolamine, potassium tert- butoxide, phosphorus oxychloride, sulfur dichloride.

10.4 Conditions to avoid

Conditions to avoid

10.5 Incompatible materials

Alkali hydroxides, halogen compounds, strong oxidizing agent, peroxy compounds, halogen oxide, alkali metals, nitrosyl compounds, metals, ethanolamine, activated charcoal, chromosulfuric acid, chromy chloride, fluorine, strong reducing agent.

Unsuitable working materials are various plastics, rubber.

10.6 Hazardous decomposition products

Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity

LD₅₀ (dermal, rabbit): 20000 mg/kg

LC₅₀ (inhalation, rat): 76 mg/l/4 h

Skin corrosion/irritation

Absorption: Slight irritations danger of skin.

Serious eye damage/eye irritation

Irritations: Risk of corneal clouding

Respiratory or skin sensitization

Dermatitis and sensitization of susceptible persons.

Germ cell mutagenicity

Not Available

Carcinogenicity

No carcinogenic in animal experiments.

Reproductive toxicity

No impairment of reproductive performance in animal experiments.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

Not Available

Aspiration hazard

Not Available

Further information

After absorption: gastrointestinal complaints, headache, salivation, nausea, vomiting, dizziness, narcosis, coma, mucosal irritations, drowsiness.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	LC ₅₀ Rainbow trout: 5540 mg/l /96h
Toxicity to daphnia and other aquatic invertebrates	EC ₅₀ Daphnia magna: 6100 mg/l /48h
Toxicity to algae	IC ₅ M.aeruginosa: 530 mg/l/8d
Toxicity to bacteria	EC ₅ Ps. Putida: 1700 mg/l /16d

12.2 Persistence and degradability

Biodegradability 91%/28 d, Readily biodegradable, according to appropriate OECD test.

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) log Pow: 0.24
No bioaccumulation is to be expected (log P o/w <1)

12.4 Mobility in soil

Not Available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

UN Number	1090
UN proper shipping name	ACETONE
Transport hazard class(es)	3
Packing group	II
Environmental hazards	No
Special precautions for user	Yes

Sea transport (IMDG)

UN Number	1090
UN proper shipping name	ACETONE
Transport hazard class(es)	3
Packing group	II
Marine pollutant	No
Special precautions for user	Yes
EmS	F-E S-D

Air transport (IATA)

UN Number	1090
UN proper shipping name	ACETONE
Transport hazard class(es)	3
Packing group	II
Environmental hazards	No
Special precautions for user	No

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or Mixture

Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany,
Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date

25/09/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.